

CONSTRUCTION PLANNING FOR THE PLACING
OF LARGE QUANTITIES OF CONCRETE

by

Kamal Abdullah Arif

A thesis submitted in partial fulfillment of the requirements for
the degree of Master of Engineering

Examination Committee: Dr. Pichai Nimityongskul (Chairman)
Dr. Ping Kunawatsatit (Co-Chairman)
Dr. R. L. Chauhan

624.183 41

ARJ

C

Kamal Abdullah Arif

Nationality : Indonesian

Previous Degree : Ir, (Sarjana Teknik Arsitektur)
Architectural Engineering Division
Parahyangan Catholic University
Bandung, Indonesia

Scholarship Donor : DAAD - German Academic Exchange Service

ASIAN INSTITUTE OF TECHNOLOGY
Bangkok, Thailand
April 1987

ABSTRACT

This study is attempted to identify the problems and to explore the more advanced of technical know-how involved in the process of large concreting work. The operational sequence, placement methods and the factors which influence the progress of concreting work on various construction projects are analysed. The types of construction included in this study are dams, bridge, underground power-house and high-rise building.

Comparisons of the results has shown that the continuous placement method yield the better output in placing of large amounts of concrete, especially for massive reinforced concrete structures. However, this method is still not widely accepted in many construction projects. It is recommended that further study be conducted on the possibility of using this method specifically for dams, underground and under water structures as well as mass foundations.

Finally, a proposed planning model and some relevant check lists are given as to provide construction planning for the placing of large quantities of concrete more meaningful.

ACKNOWLEDGEMENTS

The author wishes to express his profound gratitude to his adviser Dr. Ping Kunawatsatit who patiently gave him continuous guidance, valuable suggestions, encouragement and help from the beginning until the finalization of this thesis. Sincere thanks and appreciation are due to Dr. Pichai Nimityongskul for serving as the chairman and Dr. R. L. Chauhan as the member of his thesis examination committee.

Sincere appreciation is expressed to the DAAD-German Academic Exchange Service for providing the scholarship throughout his entire program of study and to the Asian Institute of Technology for the opportunity to study and the provision of excellent facilities.

The author also wishes to thank to Mr. Yot Laksanakoset, Project Manager of IBM Building Construction Project and Mr. Prasert Sornbutnark, Project Manager of Dao Khanong Bridge Construction Project, from Ch. Karnchang Co. Ltd, Mr. Preecha and Mr. Kunchit from Ready Mixed Division of CPAC Company, Mr. Irfan from PT. Jaya-Ohbayashi, Jakarta and Mr. Sufrizal, Site Engineer of Asahan Hydroelectric Power Construction Project, for their helps during data collection.

Special thanks are also extended to Parahyangan Catholic University especially to its present President and Vice President for academic affairs, Dr. A. Koesdarminta and Ir. Suhartono Susilo for their morale and additional financial support during the study, and to the Head of Department of Architecture, Ir. Jeffrey Kiyono M. Arch. for having permitted him to leave his job during the study.

Finally to his beloved wife, Suraya, his son Mohammad and his daughter, Keumala for their constant love, prayers and encouragement, to them this work is dedicated.

CONTENTS

CHAPTER	TITLE	PAGE
	Title Page	i
	Abstract	ii
	Acknowledgements	iii
	Contents	iv
	List of tables	v
	List of figures	vi
I.	INTRODUCTION	1
	1.1 General	1
	1.2 Statement of Problem	2
	1.3 Objectives of the Study	2
	1.4 Scope of Study	3
II.	LITERATURE REVIEW	4
	2.1 Principle of Construction Planning	4
	2.2 Process Planning Model	4
	2.3 Large Pours for Concrete Structures	5
	2.4 Heat Generation and Control	7
	2.5 The Process of Concreting	8
	2.6 Selection of Methods	11
III.	METHODOLOGY	13
	3.1 Selection of Construction Projects for Study	13
	3.2 Methods of Data Collection	14
	3.3 Data Processing and Utilization	15
IV.	CONCRETING PROCESS IN PRACTICE	16
	4.1 General	16
	4.2 IBM Building Foundation and Slab Concreting	16
	4.3 Dao Khanong Bridge Main Pile Caps Concreting	23
	4.4 BNI-46 Raft Foundation Concreting	29
	4.5 Tangga Main Dam Concreting	37
	4.6 Siguragura Main Dam and Underground Power Station Concreting	47
	4.7 Discussion and Comparison of the Concreting Practices in the Projects Observed	53
V.	PROPOSED PLANNING MODEL	57
VI.	CONCLUSIONS AND RECOMMENDATIONS	63

REFERENCES	64
TABLES	67
FIGURES	77

LIST OF TABLES

TABLES	TITLE	PAGE
4.3.1	Analysed Results of Pylon Pile Cap	67
4.3.2	Measuring Items at P3 Pile Cap	68
4.3.3	Concrete Materials of Dao Khanong Pile Cap	69
4.4.1	Methods Used for Raft Foundation Concreting	70
4.4.2	The Actual Concreting Performance of BNI-46 Raft Foundation	70
4.5.1	Tangga Main Dam Concreting Performance	71
4.5.2	Type and Quantity of Tangga Dam Measuring Apparatus	72
4.7.1	The Summary of The Data Obtained from Different Projects	73
4.7.2	The Comparison of Different Methods of Placing Concrete, Temperature Control, Supply, and Equipment Used	74
4.7.3	The Comparison of The Materials, Compressive Strength and Maximum Concrete Temperature in Different Projects	75
4.7.4	The Comparison of Production Rates and Manhours Used in Different Projects	76

List of Figures

Fig. No	Title	Page
2. 1	Cracking of Mass Concrete on Heating	77
2. 2	Cracking of Mass Concrete on Cooling	77
2. 3	Plan of Trapped Bay	77
4. 1. 1	Sectional View of IBM Building, Bangkok	78
4. 1. 2	Dao Khanong Bridge and its Main Pile Cap	79
4. 1. 3	Framing Section of BNI-46 Building, Jakarta	80
4. 1. 4	Location Map of Asahan Hydroelectric & Aluminium Project	81
4. 1. 5	General Plan of Asahan Hydroelectric Project	81
4. 1. 6	Tangga Arch Dam under Construction	82
4. 1. 7	Siguragura Gravity Dam under Construction	82
4. 1. 8	Siguragura Underground Power Station under Construction	83
4. 2. 1	Building A of IBM Project, after 70% of the Progress Completed	84
4. 2. 2	The Condition of Building B - IBM Project when Flood occurred on May 1986	84
4. 2. 3	Site Condition and Preparation for Concrete Placement of the Foundation of Building B	85
4. 2. 4	Night Time Placement of Building B foundation	85
4. 2. 5	Layout Arrangement of IBM Building foundation Concreting	86
4. 2. 6	Placement Rate of The Mat Foundation of Building B	87
4. 2. 7	56 m Vertical Pipe Line from the Concrete Pump at the Ground to 14th Floor Slab	88
4. 2. 8	24 m Horizontal Pipe Line to reach the Furthest Point	88
4. 2. 9	Layout Arrangement of 14th Floor Slab Concreting	89
4. 2. 10	Flexible hose was handled by the tower crane to distribute concrete	89
4. 2. 11	Process Chart of 14th Floor Slab Concreting	90
4. 2. 12	Flow Diagram of 14th Floor Slab Concreting	91
4. 3. 1	The Time for Completion of Placing of Each Layer and The Curing Method Used	92
4. 3. 2	Placement Rate of The Pile Cap Concreting	93
4. 3. 3	Pipe Cooling Arrangement of P3 Pile Cap	94
4. 3. 4	Pipe Cooling Arrangement of P4 Pile Cap	94
4. 3. 5	Locations of Batch Plants for Pile Caps Concreting	95
4. 3. 6	Statistical Data of CPAC Plants Production Rate in Normal Condition	96
4. 3. 7	Statistical Data of CPAC Plants Production Rate during The Placement of Dao Khanong Bridge Pile Cap	97
4. 3. 8	Site Layout Arrangement of P3 Pile Cap Concreting	98
4. 3. 9	Continuous Concrete Placing of P3 Pile Cap	99

4. 3. 10	Use of Chutes and Hopper for Concrete Placing	99
4. 3. 11	Handling the Concrete Distributor	100
4. 3. 12	Placement inside Pile cap	100
4. 3. 13	Pumping Water through the Cooling Pipe for Thermal Reduction in Concrete	101
4. 3. 14	Dense Reinforcement and Water Cooling Pipe to reduce the Heat	101
4. 4. 1	Tower Raft Foundation Block Diagram	102
4. 4. 2	Sequence Order of Concreting and Placement Schedule of BNI-46 Raft Foundation	102
4. 4. 3	Site Arrangement of Raft Foundation concreting	103
4. 4. 4	Reinforcement Installation for the Raft Foundation	103
4. 4. 5	Layout Plan of The First Method	104
4. 4. 6	Concrete Segregation caused by the improper Method	105
4. 4. 7	Placement Rate per Hour of Block 2 concreting	106
4. 4. 8	Detail of Dense Reinforcement at The Intersection Points	107
4. 4. 9	Block no. 1 after Concreting, showing Construction Joints, Water-stops and the Honey comb areas	107
4. 4. 10	Same as Fig. 4.4.9	108
4. 4. 11	Honey Comb at the Construction Joint	108
4. 4. 12	Repairing Method of Honey Comb and Cracks	109
4. 5. 1	General Plan of Construction Facilities at Tangga Dam	110
4. 5. 2	Mixing Cycle Diagram	111
4. 5. 3	3 Pours Locations (A, B & C) and The Calculation The Placing Cycle Times	111
4. 5. 4	Order of Bucket Placing for The 13th Lift of Block 5	112
4. 5. 5	Dam Body Lift Pour Progress	113
4. 5. 6	Monthly Progress of Main Dam Concreting	114
4. 5. 7	Schematic Temperature History Curve of Artificially Cooled Dam Concrete	115
4. 5. 8	Order of Joint Grouting	115
4. 5. 9	Cooling Pipe Layout Along Down Stream Face	116
4. 6. 1	Sliding Method Dam Form by 6-Ton Cableway	117
4. 6. 2	Placing Order of Siguragura Main Dam	118
4. 6. 3	Placing Under Sudden Rainfall	118
4. 6. 4	Monthly Progress of Dam Concrete Placing	119
4. 6. 5	Dam Concrete Placing Volume by Lift	120
4. 6. 6	Dumping a 2.0 m ³ bucket in stilling basin	121
4. 6. 7	Sliding steel form installation at Siguragura Dam	121
4. 6. 8	Sequence of Power House Concrete Placement	122
4. 6. 9	Arch Construction Block Diagram	123
4. 6. 10	Outline of Shaft Concrete Lining Using Slip Form	124
5. 1	Proposed Planning Model	125
5. 2	Flow Diagram of The overall Concreting Process	126

I. INTRODUCTION

1.1 General

Concrete presents unusual and different problems to the constructor. Although there is no best, right or cheapest way to place and finish concrete, good advance planning can help in choosing the proper method before any crisis occurs.

In our fast developing construction industry, the casting of large monolithical concrete structures in one continuous placement i.e. foundation of high rise building, pile cap of bridges, dam, etc. is becoming increasingly common. Uneven settlement, construction joints waterstops, and many other inconveniences are minimized or eliminated.

Some previous research has been carried out to study the actual concreting practice, e.g. TUMWATTANA (1976), in three concrete building projects in Thailand, and ALIGAEN (1983) in many projects throughout Philippines, pertaining to measuring, mixing, transporting, placing, and curing concrete. The concreting procedures were observed to be in accordance with the recommended practice. Tumwattana found that in those projects observed in Thailand the concreting practice and the quality of concrete were quite in compliance to the recommended procedures and specification, while Aligaen discovered so many faults in concreting practices in Philippines causing poor concrete quality.

Both of the studies emphasized more on the statistical concepts of quality control to evaluate the concreting practices and the concrete produced in those projects, while the amount of concrete placed were relatively small.

In this study, the construction planning, methods and procedures on concreting practice in some selected projects in Thailand and Indonesia will be observed, with particular emphasis on the process of works on placing of large amounts of concrete continuously in one time. The study is to review and to compare the methods and techniques commonly used in both ASEAN countries in order to provide guidelines for planning the applicable construction methods and procedures on this particular work.

1.2 Statement of Problem

1.2.1 Continuous Casting

For large monolithic placement, concrete supply should be as high as possible. Therefore placement time should be minimized to reduce the temperature differential induced by difference in concrete age. Placing Concrete is a "process", or "a series of actions conducted to an end", rather than just an "operation". This study will involve the entire process of production of large quantity of concrete in order to seek for the solutions of maintain the continuity of the whole process. However considering the time and financial constraints, this study will not be able to explore each section in detail and depth.

1.2.2 Heat Generation and Control

Since the obvious problem of large amounts of concrete placed is the necessity of controlling its specific behaviour, i.e. heat generation, thermal stress and cracking, and volume change, the method of construction should be carefully considered. Modern concrete technology allows us to overcome the typical problems associated with mass concrete pours, but the construction planners are often confronted with the problem of choosing the appropriate technology amongst the number of alternatives. The nature of characteristics and requirements of each alternative are varied. This problem is compounded by the condition of site and location, the nature of economy in developing countries, labor surplus, unemployment, financial instability, underutilized resources and many other things which characterize the economies of these Asean countries.

1.3 Objectives of the Study

(1) To review and interpret different construction practices on placing large amount of concrete in different types of projects in Thailand and Indonesia.

(2) To classify the problems involved in the sequence of the process and to explore the possibilities of developing the most appropriate method for placing large quantities of concrete, with the following objectives chosen for investigation :

- to reduce the cost,
- to reduce the time of construction, and
- to increase the quality of concrete produce

(3) To set up guidelines to be followed for planning the whole process of works, to perform the descriptive model of the placement operation according to the type of the project, and to evaluate the economic and the practical aspect of planning.

1.4 Scope of Study

Even though construction planning begins long before the contractor moves onto the construction site, it is beyond the scope of this study to cover all the data relating to the planning process from the design phase. The study will cover only the planning which is provided by the contractors prior and during the construction operation.

Some different types of the projects dealt with large amount of concrete placing in Thailand and Indonesia were selected as cases study, i. e:

1. IBM Office Building Construction Project in Bangkok
(Part of foundation of the 20 storeys building, with approximately 300 m³ of concrete being placed at one time)
2. Dao Khanong Cable Stayed Bridge Construction Project in Bangkok.
(The pile caps supporting the pylon, with approximately 7,000 m³ of concrete)
3. Asahan Hydroelectric Power in North Sumatera, Indonesia
 - i 38,000 m³ of concrete of Siguragura Gravity Dam
 - ii 20,000 m³ of concrete of Siguragura underground power-station
 - iii 55,000 m³ of concrete of Tangga Arch Dam
4. BNI 46 Office Building Project in Jakarta, Indonesia
(12,400 m³ of concrete of Raft Foundation of the 32 storeys concrete building).